



printhead cleaner *built in your ribbon.*

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



Wax/Resin

Technical Specifications

Color Code Tab.....	Copper
Maximum Print Speed	24 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness.....	7.6 Microns
Transmission Density	1.10
	MacBeth
	Scale
Ink Melting Point.....	70°C/158°F

NET Mark IQ



Near Edge Wax/Resin

Fast Processing

Benefits

- Specially developed for near edge printers
- Produces exceptionally black bar codes and images with no show through
- Broad stock latitude, prints well on both rough, uncoated stocks and smooth, coated stocks
- Mid-range scratch and smear resistance
- Print speeds up to 24 IPS in flexible packaging

Recommended Stock

- Coated and Uncoated
- Polyolefin (i.e. Tyvek)
- Paper Tag & Label Stocks
- Polypropylene
- Polyethylene



What you need to know to quote ribbon business.

Thermal Transfer Ribbon STORAGE CONDITIONS

For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing IIMAK thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.

*First in service. Impressions that last.*SM



310 Commerce Drive
 Amherst, NY 14228
 Call toll-free: **888.464.4625**
 Fax toll-free: **888.329.0260**

Order On-line: www.iimak.com
 Phone: **716.691.6333**
 Fax: **716.691.3395**
 Email: salesinfo@iimak.com